





Revision:	Changes:	Date:
1.0	Initial Case	2020.08.20



PINOUT ON THE 2ND PAGE

TP NOTES: 1. TP STRUCTURE: G+G 2. CG THICKNESS: 1.0mm,(Gorilla Glass) 3.SURFACE HARDNESS: 9H 3. DRIVER IC: ILI2132A 4. INTERFACE: USB; I2C; OPTIONAL UART 5. OPERATING VOLTAGE: 3.3V(CTP I2C); 5.0V(CTP USB);	GENERAL NOTES: 1. OPERATING TEMPERATURE: -20°C ~ 70°C 2. STORAGE TEMPERATURE: -30°C ~ 80°C 3. WITHOUT INDIVIDUAL TOLERANCE: ±0.3mm 4. RoHS COMPLIANT					
			PN: RVCTP70UI01 SN: DRAWN: M.Natywa 2020.08.20 1:1.52 CHECKED: Carol Gao [mm] ISO A3 P. 1 of 1			
			APPR:			



TOUCH PANNEL CONNECTOR			
Pin No.	Desc.	Pin No.	Desc.
1	USB_GND	6	I2C_VDD(3.3V)
2	USB_VDD(5.0V)	7	I2C_RST
3	USB_D-	8	I2C_SCL
4	USB_D+	9	I2C_INT
5	I2C_GND	10	I2C_SDA/TXD

CN1			
Pin No.	Desc.	Pin No.	Desc.
1	USB_VDD(5.0V)	3	USB_D+
2	USB_D-	4	USB_GND