



# Product Change Notification

Document number: RVD002-78

REV NO.	REV. DATE	CONTENTS	REMARKS
1.0	2023-12-28	First Release	

## Notification

This notice is to inform our customers of the PCN of the speaker RVA-SPK1.5W-C150. The PCN is caused by the EOL of speaker from manufacture side. New speaker RVA-SPK2.0W-C150 is released as a replacement.

Affected P/Ns:

NO.	AFFECTED PNs	NEW PNs
1	RVA-SPK1.5W-C150	RVA-SPK2.0W-C150

Below table shows the differences.

NO.	RVA-SPK1.5W-C150(EOL)	RVA-SPK2.0W-C150(NEW)
Outline dimensions	Ø20(Diameter)*5.6(Thickness)	Ø23(Diameter)*9.5(Thickness)
Rated power	1.5W	2.0W
Sound pressure level	86 ± 3dB SPL@ 0.1W (Sine wave) 0.1 m Average 1000,1200,1500,2000Hz	88 ± 3dB @ 0.1W (Sine wave) 0.1 m Average 800,1000,1200,1500Hz
Rated impedance	8.0 ± 15%ohms @2kHz, 1V rms input	4.0 ± 15%ohms @1kHz, 1V rms input
Rated frequency range	20Hz – 10 kHz	50Hz – 10 kHz
Operating temperature	-20°C to 55 °C	-10°C to 60 °C

Hi, I am here to help you!  
If you have any additional questions, please contact our support via email: [contact@riverdi.com](mailto:contact@riverdi.com)

