

SSD1963 4.3"



This datasheet gives detailed information about the Riverdi 4.3" SSD1963 displays. The displays come in different versions: with **capacitive, resistive, or no touchscreen**, with a decorative **cover glass**, as well as with our without a **metal mounting frame**.

ORDER NOW



Rev.1.0
2019-06-07

ITEM	CONTENTS	UNIT
LCD Type	TFT/Transmissive/Normally white	/
Size	4.3	Inch
Viewing Direction	12:00 (without image inversion)	O' Clock
Gray Scale Inversion Direction	6:00	O' Clock

Number of Dots		480 x (RGB) × 272	/
Driver IC		SSD1963	/
Interface Type		Parallel 8/16b (i80 by default) – SPI	/
Brightness	no touch module	550	cd/m2
	CTP module	500	
	RTP module	440	
Color Depth		16.7M	/
Pixel Arrangement		RGB Vertical Stripe	/
Surface Treatment		Anti-glare / Clear (for CTP)	/
Input Voltage		3.3	V

Note 1: RoHS, REACH SVHC compliant

Note 2: LCM weight tolerance: ± 5%.

Revision Record

REV NO.	REVDATE	CONTENTS	REMARKS
1.0	2019-06-07	Initial Release	

Table of Content

1. Module classification information	10.1. Electrical characteristics
2. Assembly guide – integration	10.1.1. For capacitive touch panel
2.1. Mounting frame	10.1.2. For resistive touch panel
3. Module drawings	10.2. Mechanical characteristics
4. Absolute maximum ratings	10.2.1. Mechanical For capacitive touch panel
5. Electrical characteristics	10.2.2. Mechanical For resistive touch panel
6. Electro-optical characteristics	10.3. Capacitive touch panel parameters
7. Interface description	10.3.1. Interface timing characteristics
8. Interface timing characteristics	10.3.2. I2C Read/Write Interface description
8.1. 8080 mode	10.3.3. Communication of the I2C interface with host
8.2. Parallel 8080-series Interface Timing	10.3.4. Touch data read protocol
9. LCD timing characteristics	10.3.5. Data description
9.1. For parallel RGB input timing table	10.3.6. Interrupt Trigger Mode
9.2. 24Bit GB Mode for 320xRGBx240	11 Inspection
10 Touch panel specifications	11.1. Inspection condition
	11.2. Inspection standard

1. Module classification information

RV	T	4.3	A	480 272	C	x	W	x	36
1.	2.	3.	4.	5.	6.	7.	8.	9.	10.

1.	BRAND	RV – Riverdi
2.	PRODUCT TYPE	T – TFT Standard
3.	DISPLAY SIZE	4.3 – 4.3"
4.	MODEL SERIAL NO.	A (A-Z)
5.	RESOLUTION	480272– 480×272 px
6.	INTERFACE	C – TFT+SSD1963
7.	FRAME	N – No Frame F – Mounting Frame
8.	BACKLIGHT TYPE	W – LED White
9.	TOUCH PANEL	N – No Touch Panel R – Resistive Touch Panel C – Capacitive Touch Panel
10.	VERSION	36 (00-99)

2. Assembly guide – integration

Three options of rear side adhesive tape are available: double side adhesive tape 0.2 mm with 3M 467MP glue, foam double side adhesive tape 0.5 mm with DST 3M 9495LE glue or without any tape.



There are also two versions of glass color: black and white.

Rear side adhesive tape options:

		
Double side adhesive tape with DST 3M 9495LE glue	Foam double side adhesive tape with 3M 9495LE glue	Without tape

(total thickness 0.2mm)	(total thickness 0.5mm)	
-------------------------	-------------------------	--

Cover glass color options:

	
BLACK	WHITE

Product options:


PART NUMBER	DESCRIPTION
RVT43ULSNWC00	SSD1963, CTP uxTouch, black cover glass, 0.2 mm DST
RVT43ULSNWC01	SSD1963, CTP uxTouch, black cover glass, 0.5 mm DST
RVT43ULSNWC02	SSD1963, CTP uxTouch, black cover glass, no DST
RVT43ULSNWC03	SSD1963, CTP uxTouch, white cover glass, 0.2mm DST
RVT43ULSNWC04	SSD1963, CTP uxTouch, white cover glass, 0.5 mm DST
RVT43ULSNWC05	SSD1963, CTP uxTouch, white cover glass, no DST

2.1. UxTouch assembly

UxTouch are LCD TFT displays with specially designed projected capacitive touch panels. UxTouch display can be mounted without any hole in the housing. Our standard UxTouch displays include double-sided adhesive tape (DST) to stick TFT easily to the housing.

UxTouch models with double-side adhesive tape (PN with endings 00, 01, 03, 04) can be mounted by connecting the glass to the housing. Riverdi recommends to use support brackets assembled to display's back. An additional support will stiffen the whole structure and minimize the influence of external factors such as vibration. Figure 1 and Figure 2 below show examples of using support elements.



Figure 1. Example of using support brackets







2.2. Mounting frame

Thanks to the four catches attached to the side, frame provides strong assembly to the surface by mounting element (like the screw, see Figure 3). The frames are specially designed to fit Riverdi products perfectly. The diameter of the mounting hole is 3.5mm.

Figure 2. Mounting frame







4. Absolute maximum ratings

PARAMETER	SYMBOL	MIN	MAX	UNIT
Supply Voltage for Logic	VDD	-0.3	4.6	V
Input Voltage for Logic	VIN	-0.3	VDD	V
Input voltage for LED inverter	BLVDD	-0.3	7.0	V
Operating Temperature	TOP	-20	70	°C
Storage Temperature	TST	-30	80	°C
Humidity	RH	–	90% (Max 60°C)	RH

5. Electrical characteristics

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	NOTES
Supply Voltage For Module	VDD	3.0	3.3	3.6	V	
Input Voltage for LED Inverter	BLVDD	2.8	3.3	5.5	V	
Input Voltage 'H' level for BL_E pin	BL_Eh	1.5	–	5.5	V	
Input Voltage 'L' level for BL_E pin	BL_El	0	–	0.7	V	
Input current (exclude LED backlight)	IDD	–	25	32	mA	VDD=3.3V
LED backlight current	IDDbacklight	–	265	332	mA	BLDD=3.3v
LED backlight current	IDDbacklight	–	156	195	mA	BLDD=5v
Total Input Current (Include LED backlight 100%)	IDDtotal	–	290	363	mA	BLVDD=3.3V
Input Voltage 'H' level	Vih	0.7VDD	–	VDD	V	
Input Voltage 'L' level	Vil	0	–	0.2VDD	V	
LED Life Time	–	30000	50000	–	Hrs	Note1

Note1: The LED life time is defined as the module brightness decrease to 50% original brightness at Ta=25°C

6. Electro-optical characteristics

ITEM	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT	REMARK	NOTE
Response Time	Tr+Tf	$\theta=0^\circ$ $\phi=0^\circ$ Ta=25	–	20	30	ms	Figure 1	4
Contrast Ratio	Cr		320	400	–	—	Figure 2	1
Luminance Uniformity	δ WHITE		80	–	–	%	Figure 2	3
Surface Luminance	TFT		–	550	–	cd/m2	Figure 2	2
	TFT+CTP		–	500	–			
	TFT+RTP		–	440	–			

Viewing Angle Range		θ	$\varnothing = 90^\circ$	35	50	–	deg	Figure 3	6
			$\varnothing = 270^\circ$	55	70	–	deg	Figure 3	
			$\varnothing = 0^\circ$	55	70	–	deg	Figure 3	
			$\varnothing = 180^\circ$	55	70	–	deg	Figure 3	
CIE (x, y) Chromaticity	Red	x	$\theta=0^\circ$ $\varnothing=0^\circ$ Ta=25	0.57	0.620	0.670	Figure 2		5
		y		0.294	0.344	0.394			
	Green	x		0.256	0.306	0.356			
		y		0.513	0.563	0.613			
	Blue	x		0.083	0.133	0.183			
		y		0.099	0.149	0.199			
	White	x		0.25	0.300	0.350			
		y		0.28	0.330	0.380			

Note 1. Contrast Ratio(CR) is defined mathematically as below, for more information see Figure 4 .

$$\text{Contrast Ratio} = \frac{\text{Average Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}{\text{Average Surface Luminance with all black pixels (P1, P2, P3, P4, P5)}}$$

Note 2. Surface luminance is the LCD surface from the surface with all pixels displaying white. For more information, see Figure 4 .

$$Lv = \text{Average Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}$$

Note 3. The uniformity in surface luminance δ WHITE is determined by measuring luminance at each test position 1 through 5, and then dividing the maximum luminance of 5 points luminance by minimum luminance of 5 points luminance. For more information, see Figure 4 .

$$\delta \text{ WHITE} = \frac{\text{Minimum Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}{\text{Maximum Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}$$

Note 4. Response time is the time required for the display to transition from white to black (Rise Time, Tr) and from black to white (Decay Time, Tf). For additional information see FIG 1. The test equipment is Autronic-Melchers's ConoScope series.

Note 5. CIE (x, y) chromaticity, the x, y value is determined by measuring luminance at each test position 1 through 5, and then make average value.

Note 6. Viewing angle is the angle at which the contrast ratio is greater than 2. For TFT module the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see Figure 4.

Note 7. For viewing angle and response time testing, the testing data is based on Autronic-Melchers's ConoScope series. Instruments for Contrast Ratio, Surface Luminance, Luminance Uniformity, CIE the test data is based on TOPCON's BM-5 photo detector.

Note 8. For TFT module, Gray scale reverse occurs in the direction of panel viewing angle.

Figure 3. The definition of response time




Figure 4. Measuring method for Contrast ratio, surface luminance, Luminance uniformity, CIE (x, y) chromaticity





Figure 5. The definition of viewing angle



7. Interface description

PIN NO.	SYMBOL	I/O	DESCRIPTION
1	GND	P	Power Ground
2	VDD	P	Power Supply: +3.3V
3	BL_E	I	Backlight Control Signal, H: On/L: Off (internally pulled-up to BLVDD)
4	D/C	I	Data/Command Select
5	WR	I	Write Strobe Signal
6	RD	I	Read Strobe Signal
7-22	D0-D15	I	Data Bus. Pins not used should be floating.
23	NC	–	No Connection
24	TP_INT (CTP module)	O	Touch Panel INT
	NC (RTP module)	–	No Connection
	NC (no touch module)	–	No Connection
25	CS	I	Chip Select
26	RESET	I	Hardware reset
27	DISP ON	I	Display Control H: On/L: Off (internally pulled-up)
28	NC	–	No Connection
29	TP_SCL (CTP module)	I/O	Touch Panel I2C SCL Signal
	XR (RTP module)	–	Touch right electrode
	NC (no touch module)	–	No Connection
30	TP_SDA (CTP module)	I/O	Touch Panel I2C SDA Signal
	YD (RTP module)	–	Touch down electrode
	NC (no touch module)	–	No Connection

31	TP_RST (CTP module)	I	Touch Panel RST Signal, Active Low
	XL (RTP module)	–	Touch left electrode
	NC (no touch module)	–	No Connection
32	NC (CTP module)	–	No Connection
	YU (RTP module)	–	Touch up electrode
	NC (no touch module)	–	No Connection
33	BLGND	P	Backlight ground, can be connected to GND
34	BLGND	P	Backlight ground, can be connected to GND
35	BLVDD	P	Backlight power supply, can be connected to VDD
36	BLVDD	P	Backlight power supply, can be connected to VDD

8. Interface timing characteristics

8.1. 8080 mode

The 8080 mode MCU interface consist of CS#, D/C#, RD#, WR#, D[15:0]. This interface uses WR# to define a write cycle and RD# for read cycle. If the WR# goes low when the CS# signal is low, the data or command will be latched into the system at the rising edge of WR#. Similarly, the read cycle will start when RD# goes low and end at the rising edge of RD#.

Interface	Cycle	D[17]	D[16]	D[15]	D[14]	D[13]	D[12]	D[11]	D[10]	D[9]	D[8]	D[7]	D[6]	D[5]	D[4]
16 bits (565 format)	1 st			R5	R4	R3	R2	R1	G5	G4	G3	G2	G1	G0	B5
16 bits	1 st			R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4
	2 nd			B7	B6	B5	B4	B3	B2	B1	B0	R7	R6	R5	R4
	3 rd			G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4
12 bits	1 st							R7	R6	R5	R4	R3	R2	R1	R0
	2 nd							G3	G2	G1	G0	B7	B6	B5	B4
9 bits	1 st										R5	R4	R3	R2	R1
	2 nd										G2	G1	G0	B5	B4
8 bits	1 st											R7	R6	R5	R4
	2 nd											G7	G6	G5	G4
	3 rd											B7	B6	B5	B4

8.2. Parallel 8080-series Interface Timing

Figure 6. Parallel 8080-series Interface Timing Diagram (Write Cycle)





Figure 7.Parallel 8080-series Interface Timing Diagram (Read Cycle)



9. LCD timing characteristics


9.1. For parallel RGB input timing table

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
-----------	--------	-----	-----	-----	------

DCLK Frequency	Fclk	5	9	12	MHz
VSD Period Time	Tv	277	288	400	H
VSD Display Area	Tvd	272			H
VSD Back Porch	Tvb	3	8	31	H
VSD Front Porch	Tvfp	2	8	97	H
HSD Period Time	Th	520	525	800	DCLK
HSD Display Area	Thd	480			DCLK
HSD Back Porch	Thbp	36	40	255	DCLK
HSD Front Porch	Thfp	4	5	65	DCLK

9.2. Clock and data input time diagram

Figure 8. Clock and data input time diagram



10. Touch panel specifications

10.1. Electrical characteristics

Note: Avoid operating with hard or sharp material such as a ball point pen or a mechanical pencil except a polyacetal pen (tip R0.8mm or less) or a finger

10.1.1. For capacitive touch panel


DESCRIPTION		SPECIFICATION
Operating Voltage		DC 2.8~3.6V
Power Consumption (IDD)	Active Mode	10~18mA
	Sleep Mode	30~50μA
Interface		I ² C
Linearity		<1.5%
Controller		FT5446
I2C address		0x38 (7 bit address)
Resolution		1280*768

10.1.2. For resistive touch panel

ITEM	VALUE			UNIT	REMARK
	Min.	Typ.	Max.		
Linearity	-3.0	–	1.5	%	Analog X and Y directions
Terminal Resistance	200	–	900	Ω	X
	100	–	600	Ω	Y
Insulation Resistance	20	–	–	MΩ	DC 25V
Voltage	–	–	10	V	DC
Chattering	–	–	10	ms	100kΩ pull-up
Transparency	78	–	–	%	JIS K7105

10.2. Mechanical characteristics

Note 1: Force test condition, Input DC 5V on X direction, Drop off Polyacetal Stylus (R0.8), until output voltage stabilize, then get the R8.0mm Silicon rubber and do finger Activation force test. Next step, 9 points.



Note 2: Measurement surface area conditions, Scratch 100,000 times straight line on the film with a stylus change every 20,000 times with Force: 250gf, Speed: 60mm/sec by R0.8 polaceteal

stylus.

Note 3: Pitting test, Pit 1, 000, 000 times on the film with R0.8 silicon rubber with Force: 250gf and Speed: 2 times/sec.

10.2.1 for capacitive touch panel

DESCRIPTION	INL SPECIFICATION	REMARK
Touch Panel Size	4.3 inch	
Outline Dimension (OD)	104.0mm x 65.4mm	Cover Lens Outline
Outline Dimension (OD) -UxTouch	120.38mm x 79.20mm	Cover Lens Outline
Product Thickness	1.7mm	
Glass Thickness	0.7mm	
Ink View Area	96.54mm x 55.36mm	
Sensor Active Area	98.0mm x 56.5mm	
Input Method	5 Finger	
Activation Force	Touch	
Surface Hardness	≥7H	

10.2.2. For resistive touch panel

Note 1: Force test condition, Input DC 5V on X direction, drop off Polyacetal Stylus (R0.8), until output voltage stabilize, then get the R8.0mm Silicon rubber and do finger Activation force test. Next step, 9 points.

ITEM	VALUE			UNIT	REMARK
	Min.	Typ.	Max.		
Activation Force	20	–	–	gf	Note 1
Durability-Surface Scratching	Write 100,000	–	–	characters	Note 2
Durability-Surface Pitting	1,000,000	–	–	touches	Note 3
Surface Hardness	3	–	–	H	JIS K5400

10.3. Capacitive touch panel parameters

10.3.1. Interface timing characteristics

PARAMETER	MIN	MAX	UNIT
SCL Frequency	0	400	kHz
Bus Free Time Between a STOP and START Condition	4.7	/	µs
Hold Time (repeated) START Condition	4.0	/	µs
Data Setup Time	250	/	ns
Setup Time for Repeated START Condition	4.7	/	µs
Setup Time for STOP Condition	4.0	/	µs

10.3.2. I2C Read/Write Interface description

Figure 9. Write N bytes to I2C slave




Figure 10. Set Data Address





Figure 11. Read X bytes from I2C Slave



10.3.3. Communication of the I2C interface with host

Figure 12. Communication of the I2C interface with Host

17h	TOUCH4_YH	4th Touch ID[3:0]				4th Touch X Position[11:8]				R
18h	TOUCH4_YL	4th Touch Y Position[7:0]								R
19h										R
1Ah										R
1Bh	TOUCH5_XH	5th Event Flag				5th Touch X Position[11:8]				R
1Ch	TOUCH5_XL	5th Touch X Position[7:0]								R
1Dh	TOUCH5_YH	5th Touch ID[3:0]				5th Touch X Position[11:8]				R
1Eh	TOUCH5_YL	5th Touch Y Position[7:0]								R

10.3.5 Data description

DEVICE_MODE

This register is the device mode register, configure it to determine the current mode of the chip.

ADRESS	BIT ADDRESS	REGISTER NAME	DESCRIPTION
00h	6:4	Device Mode [2:0]	000b Work Mode 100b Factory Mode – Read Raw Data

GEST_ID

This register describes the gesture of a valid touch.

ADRESS	BIT ADDRESS	REGISTER NAME	DESCRIPTION
01h	7:0	Gesture ID [7:0]	Gesture ID 0x10 Move Up 0x14 Move Down 0x18 Move Right 0x48 Zoom In 0x49 Zoom Out 0x00 No Gesture

TD_STATUS

This register is the Touch Data status register.

ADRESS	BIT ADDRESS	REGISTER NAME	DESCRIPTION
02h	3:0	Number of Touch Points [2:0]	How Many Points Detected 1-5 is Valid
	7:4		

TOUCHn_XH(n:1-10)

This register describes MSB of the X coordinate of the nth touch point and the corresponding event flag.

ADRESS	BIT ADRESS	REGISTER NAME	DESCRIPTION
03h ~ 39h	7:6	Event Flag	00b: Put Down 01b: Put Up 10b: Contact 11b: Reserved
	5:4		Reserved
	3:0	Touch X Position [11:8]	MSB of Touch X Position in Pixels

TOUCHn_XL(n:1-10)

This register describes LSB of the X coordinate of the nth touch point.

ADRESS	BIT ADRESS	REGISTER NAME	DESCRIPTION
04h ~ 3Ah	7:0	Touch X Position [7:0]	LSB of the Touch X Position in Pixels

TOUCHn_YH(n:1-10)

This register describes MSB of the Y coordinate of the nth touch point and corresponding touch ID.

ADRESS	BIT ADRESS	REGISTER NAME	DESCRIPTION
05h ~ 3Bh	7:4	Touch ID[3:0]	Touch ID of Touch Point
	3:0	Touch X Position [11:8]	MSB of Touch Y Position in Pixels


TOUCHn_YL(n:1-10)

This register describes LSB of the Y coordinate of the nth touch point.

ADRESS	BIT ADRESS	REGISTER NAME	DESCRIPTION
05h ~ 3Bh	7:0	Touch X Position [7:0]	LSB of the Touch Y Position in Pixels

10.3.6 Interrupt Trigger Mode

Figure 13. Interrupt trigger mode timing



11. Inspection

Standard acceptance/rejection criteria for TFT module.

11.1. Inspection condition

Ambient conditions:

- Temperature: $25\pm^{\circ}\text{C}$
- Humidity: $(60\pm 10)\ \% \text{RH}$
- Illumination: Single fluorescent lamp non-directive (300 to 700 lux)


Viewing distance:

$35\pm 5\text{cm}$ between inspector bare eye and LCD.

Viewing Angle:

U/D: $45^{\circ}/45^{\circ}$, L/R $45^{\circ}/45^{\circ}$

LCD black spots,
white spots, light
leakage (line Type)



*Spots density: 10 mm

Size < 5"		
Length	Width	Qualified Qty
–	W< 0.02	Ignored
L < 3.0	0.02 < W <0.05	2
L < 2.5	0.05 < W <0.08	
–	0.08 < W	0

Size >= 5"		
Length	Width	Qualified Qty
–	W< 0.02	Ignored
L < 3.0	0.02 < W <0.05	4
L < 2.5	0.05 < W <0.08	
–	0.08 < W	0

Item	Criterion
------	-----------

Clear spots

Size < 5"	
Average Diameter	Qualified Qty
D < 0.2 mm	Ignored
0.2 mm < D < 0.3 mm	3
0.3 mm < D < 0.5 mm	2
0.5 mm < D	0

Size >= 5"	
Average Diameter	Qualified Qty
D<0.2 mm	Ignored
0.2 mm < D < 0.3 mm	4
0.3 mm < D < 0.5 mm	2
0.5 mm < D	0

*Spots density: 10 mm

Polarizer bubbles

Size < 5"	
Average Diameter	Qualified Qty
D < 0.2 mm	Ignored
0.2 mm < D < 0.5 mm	3
0.5 mm < D < 1 mm	2
1 mm < D	0
Total Q'ty	3

Size >= 5"	
Average Diameter	Qualified Qty

	<table><tr><td>D<0.25 mm</td><td>Ignored</td></tr><tr><td>0.25 mm < D < 0.5 mm</td><td>3</td></tr><tr><td>0.5 mm < D</td><td>0</td></tr></table>	D<0.25 mm	Ignored	0.25 mm < D < 0.5 mm	3	0.5 mm < D	0																										
D<0.25 mm	Ignored																																
0.25 mm < D < 0.5 mm	3																																
0.5 mm < D	0																																
Electrical Dot Defect	<table><tr><td colspan="2">Size < 5"</td></tr><tr><td>item</td><td>Qualified Qty</td></tr><tr><td>Black do defect</td><td>4</td></tr><tr><td>Bright dot defect</td><td>2</td></tr><tr><td>Total Dot</td><td>5</td></tr></table> <table><tr><td colspan="2">Size >= 5"</td></tr><tr><td>item</td><td>Qualified Qty</td></tr><tr><td>Black do defect</td><td>5</td></tr><tr><td>Bright dot defect</td><td>2</td></tr><tr><td>Total Dot</td><td>5</td></tr></table>	Size < 5"		item	Qualified Qty	Black do defect	4	Bright dot defect	2	Total Dot	5	Size >= 5"		item	Qualified Qty	Black do defect	5	Bright dot defect	2	Total Dot	5												
Size < 5"																																	
item	Qualified Qty																																
Black do defect	4																																
Bright dot defect	2																																
Total Dot	5																																
Size >= 5"																																	
item	Qualified Qty																																
Black do defect	5																																
Bright dot defect	2																																
Total Dot	5																																
Item	Criterion																																
Touch panel spot	<table><tr><td colspan="2">Size < 5"</td></tr><tr><td>Average Diameter</td><td>Qualified Qty</td></tr><tr><td>D < 0.2 mm</td><td>Ignored</td></tr><tr><td>0.2 mm < D < 0.4 mm</td><td>5</td></tr><tr><td>0.4 mm < D < 0.5 mm</td><td>2</td></tr><tr><td>0.5 mm < D</td><td>0</td></tr></table> <table><tr><td colspan="2">Size >= 5"</td></tr><tr><td>Average Diameter</td><td>Qualified Qty</td></tr><tr><td>D<0.25 mm</td><td>Ignored</td></tr><tr><td>0.25 mm < D < 0.5 mm</td><td>4</td></tr><tr><td>0.5 mm < D</td><td>0</td></tr></table>	Size < 5"		Average Diameter	Qualified Qty	D < 0.2 mm	Ignored	0.2 mm < D < 0.4 mm	5	0.4 mm < D < 0.5 mm	2	0.5 mm < D	0	Size >= 5"		Average Diameter	Qualified Qty	D<0.25 mm	Ignored	0.25 mm < D < 0.5 mm	4	0.5 mm < D	0										
Size < 5"																																	
Average Diameter	Qualified Qty																																
D < 0.2 mm	Ignored																																
0.2 mm < D < 0.4 mm	5																																
0.4 mm < D < 0.5 mm	2																																
0.5 mm < D	0																																
Size >= 5"																																	
Average Diameter	Qualified Qty																																
D<0.25 mm	Ignored																																
0.25 mm < D < 0.5 mm	4																																
0.5 mm < D	0																																
Touch panel White Line Scratch	<table><tr><td colspan="2">Size < 5"</td><td></td></tr><tr><td>Length</td><td>Width</td><td>Qualified Qty</td></tr><tr><td>–</td><td>W< 0.02</td><td>Ignored</td></tr><tr><td>L < 3.0</td><td>0.02 < W <0.05</td><td rowspan="2">2</td></tr><tr><td>L < 2.5</td><td>0.05 < W <0.08</td></tr><tr><td>–</td><td>0.08 < W</td><td>0</td></tr></table> <table><tr><td colspan="2">Size >= 5"</td><td></td></tr><tr><td>Length</td><td>Width</td><td>Qualified Qty</td></tr><tr><td>–</td><td>W< 0.03</td><td>Ignored</td></tr><tr><td>L < 5.0</td><td>0.03 < W <0.05</td><td>2</td></tr><tr><td>–</td><td>0.05 < W</td><td>0</td></tr></table>	Size < 5"			Length	Width	Qualified Qty	–	W< 0.02	Ignored	L < 3.0	0.02 < W <0.05	2	L < 2.5	0.05 < W <0.08	–	0.08 < W	0	Size >= 5"			Length	Width	Qualified Qty	–	W< 0.03	Ignored	L < 5.0	0.03 < W <0.05	2	–	0.05 < W	0
Size < 5"																																	
Length	Width	Qualified Qty																															
–	W< 0.02	Ignored																															
L < 3.0	0.02 < W <0.05	2																															
L < 2.5	0.05 < W <0.08																																
–	0.08 < W	0																															
Size >= 5"																																	
Length	Width	Qualified Qty																															
–	W< 0.03	Ignored																															
L < 5.0	0.03 < W <0.05	2																															
–	0.05 < W	0																															

12. Reliability test

NO.	TEST ITEM	TEST CONDITION	INSPECTION AFTER TEST
1	High Temperature Storage	80±2°C/240 hours	<p>Inspection after 2~4 hours storage at room temperature, the sample shall be free from defects:</p> <ol style="list-style-type: none"> 1. Air bubble in the LCD 2. Seal leak 3. Non-display 4. Missing segments 5. Glass crack 6. Current Idd is twice higher than initial value 7. The surface shall be free from damage 8. Linearity must be no more than 1.5% by the linearity tester 9. The Electric characteristics requirements shall be satisfied
2	Low Temperature Storage	-30±2°C/240 hours	
3	High Temperature Operating	70±2°C/240 hours	
4	Low Temperature Operating	-20±2°C/240 hours	
5	Temperature Cycle	-30±2°C~25~70±2°C × 30 cycles	
6	Damp Proof Test	60°C ±5°C × 90%RH/160 hours	
7	Vibration Test	Frequency 10Hz~55Hz Stroke: 1.5mm Sweep: 10Hz~55Hz~10Hz 2 hours For each direction of X, Y, Z (6 hours for total)	
8	Mechanical Shock	60G 6ms, ± X, ± Y, ± Z 3 times for each direction	
9	Packing Drop Test	Height: 80 cm 1 corner, 3 edges, 6 surfaces	
10	Package Vibration Test	Random vibration: 0.015G ² /Hz from 5-200Hz -6dB/Octave from 200-500Hz 2 hours for each direction of X, Y, Z (6 hours for total)	
11	Electrostatic Discharge	Air: ±8KV 150pF/330Ω 5 times Contact: ±4KV 150pF/330Ω 5 times	

12	Hitting Test	<p>1,000,000 times in the same point</p> <p>Hitting pad: tip R3.75mm, Silicone rubber, Hardness: 40deg.</p> <p>Load: 2.45N</p> <p>Hitting speed: Twice/sec</p> <p>Electric load: none</p> <p>Test area should be at 1.8mm inside of insulation.</p>
13	Pen Sliding Durability Test	<p>100,000 times minimum</p> <p>Hitting pad: tip R0.8mm plastic pen</p> <p>Load: 1.47N</p> <p>Sliding speed: 60 mm/sec</p> <p>Electric load: none</p> <p>Test area should be at 1.8mm inside of insulation.</p>
<p>Remark:</p> <p>1. The test samples should be applied to only one test item.</p> <p>2. Sample size for each test item is 5~10pcs.</p> <p>3. For Damp Proof Test, Pure water(Resistance 10MΩ) should be used.</p> <p>4. In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judge as a good part.</p> <p>5. EL evaluation should be excepted from reliability test with humidity and temperature: Some defects such as black spot/blemish can happen by natural chemical reaction with humidity and Fluorescence EL has.</p> <p>6. Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic.</p>		

Note 1: Without water condensation.

Note 2: The function test shall be conducted after 2 hours storage at the room temperature and humidity after removed from the test chamber.



✉ Still stuck [How can we help](#)

Updated on April 30, 2020

Was this article helpful to you

Yes

No